

BEST AVAILABLE COPY

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: G02B		(11) International Publication Number: WO 99/08134
A2		(43) International Publication Date: 18 February 1999 (18.02.99)
(21) International Application Number: PCT/US98/16568 (22) International Filing Date: 7 August 1998 (07.08.98) (30) Priority Data: 08/908,247 7 August 1997 (07.08.97) US (71) Applicant: KLA-TENCOR, INC. [US/US]; 160 Rio Robles, San Jose, CA 95161-1809 (US). (72) Inventors: SHAFER, David, Ross; 56 Drake Lane, Fairfield, CT 06430 (US). CHUANG, Yung-Ho; 10679 Farallone Drive, Cupertino, CA 95014 (US). TSAI, Bin-Ming, Benjamin; 19801 Scotland Drive, Saratoga, CA 95070 (US). (74) Agents: FERRELL, John, S. et al.; Carr & Ferrell LLP, Suite 200, 2225 East Bayshore Road, Palo Alto, CA 94303 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>

(54) Title: **ULTRA-BROADBAND UV MICROSCOPE IMAGING SYSTEM WITH WIDE RANGE ZOOM CAPABILITY**



(57) Abstract

An ultra-broadband ultraviolet (UV) catadioptric imaging microscope system with wide-range zoom capability. The microscope system, which comprises a catadioptric lens group and a zooming tube lens group, has high optical resolution in the deep UV wavelengths, continuously adjustable magnification, and a high numerical aperture. The system integrates microscope modules, such as objectives, tube lenses and zoom optics to reduce the number of components, and to simplify the system manufacturing process. The preferred embodiment offers excellent image quality across a very broad deep ultraviolet spectral range, combined with an all-refractive zooming tube lens. The zooming tube lens is modified to compensate for higher-order chromatic aberrations that would normally limit performance.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

ULTRA-BROADBAND UV MICROSCOPE IMAGING SYSTEM WITH WIDE RANGE ZOOM CAPABILITY

BACKGROUND OF THE INVENTION

5

1. Field of the Invention

This invention relates generally to an ultra-broadband ultraviolet (UV) catadioptric imaging microscope system, and more specifically to an imaging
10 system that comprises a UV catadioptric objective lens group and a wide-range zooming tube lens group.

2. Description of the Prior Art

15 Catadioptric imaging systems for the deep ultraviolet spectral region (about 0.19 to 0.30 micron wavelength) are known. U.S. Pat. No. 5,031,976 to Shafer and U.S. Pat. No. 5,488,229 to Elliott and Shafer disclose two such systems. These systems employ the Schupmann achromatic lens principle and the Offner-type field lens. Axial color and primary lateral color are corrected, but not higher
20 order lateral color. This is the limiting aberration in these systems when a broad spectral range is covered.

The above-noted '976 Shafer patent discloses an optical system based on the Schupmann achromatic lens principle which produces an achromatic virtual
25 image. A reflective relay then creates an achromatic real image from this virtual image. The system, reproduced here as FIG. 1, includes an aberration corrector group of lenses 101 for correcting image aberrations and chromatic variation of image aberrations, a focusing lens 103 for receiving light from the group 101 and producing an intermediate image at plane 105, a field lens 107 of the same material as the other lenses placed at the intermediate image plane 105, a thick
30 lens 109 with a plane mirror back coating 111 whose power and position are

selected to correct the primary longitudinal color of the system in conjunction with the focusing lens 103, and a spherical mirror 113 located between the intermediate image plane and the thick lens 109 for producing a final image 115. Most of the focusing power of the system is due to the spherical mirror 113 which has a small central hole near the intermediate image plane 105 to allow light from the intermediate image plane 105 to pass through to the thick lens 109. The mirror coating 111 on the back of the thick lens 109 also has a small central hole 119 to allow light focused by the spherical mirror 113 to pass through to the final image 115. While primary longitudinal (axial) color is corrected by the thick lens 109, the Offner-type field lens 107 placed at the intermediate image 105 has a positive power to correct secondary longitudinal color. Placing the field lens slightly to one side of the intermediate image 105 corrects tertiary longitudinal color. Thus, axial chromatic aberrations are completely corrected over a broad spectral range. The system also incidentally corrects for narrow band lateral color, but fails to provide complete corrections of residual (secondary and higher order) lateral color over a broad UV spectrum.

The above-noted '229 patent to Elliott and Shafer provides a modified version of the optical system of the '976 patent, which has been optimized for use in .193-micron wavelength high power excimer laser applications such as ablation of a surface 121' as seen in FIG. 2. This prior art system has an aberration corrector group 101', focusing lens 103', intermediate focus 105', field lens 107', thick lens 109', mirror surfaces 111' and 113' with small central opening 117' and 119' therein and a final focus 115' as in the prior '976 patent, but repositions the field lens 107' so that the intermediate image or focus 105' lies outside of the field lens 107' to avoid thermal damage from the high power densities produced by focusing the excimer laser light. Further, both mirror surfaces 111' and 113' are formed on lens elements 108' and 109'. The combination of all light passing through both lens elements 108' and 109' provides the same primary longitudinal color correction of the single thick lens 109 in FIG. 1, but with a reduction in total glass thickness. Since even fused silica begins to have absorption problems at the

very short 0.193 micron wavelength, the thickness reductions is advantageous at this wavelength for high power levels. Though the excimer laser source used for this optical system has a relatively narrow spectral line width, the dispersion of silica near the 0.193 micron wavelength is great enough that some color
5 correction is still needed. Both prior art systems have a numerical aperture of about 0.6.

Longitudinal chromatic aberration (axial color) is an axial shift in the focus position with wavelength. The prior art system seen in FIG. 1 completely corrects for primary, secondary and tertiary axial color over a broad wavelength
10 band in the near and deep ultraviolet (0.2 micron to 0.4 micron region). Lateral color is a change in magnification or image size with wavelength, and is not related to axial color. The prior art system of FIG. 1 completely corrects for primary lateral color, but not for residual lateral color. This is the limiting aberration in the system when a broad spectral range is covered.

15 U.S. Pat. No. 5,717,518 is for a catadioptric UV imaging system with performance improved over the systems of the above-describe patents. This system employs an achromatized field lens group to correct for secondary and higher order lateral color, which permits designing a high NA, large field, ultra-broadband UV imaging system.

20 Zooming systems in the visible wavelengths are well-known. They either do not require very high levels of correction of higher-order color effects over a broad spectral region, or do require correction, but accomplish this by using three or more glass types. In the deep UV, there are very few materials that can be used for chromatic aberration correction, making the design of high performance,
25 broadband optics difficult. It is even more difficult to correct for chromatic aberrations for ultra-broadband optics with wide-range zoom.

There remains, therefore, a need for an ultra-broadband UV microscope imaging system with wide-range zoom capability.

SUMMARY OF THE INVENTION

The present invention has an object to provide a catadioptric imaging system which corrects for image aberrations, chromatic variation of image
5 aberrations, longitudinal (axial) color and lateral color, including residual (secondary and higher order) lateral color correction over an ultra-broad spectral range in the near and deep UV spectral band (0.2 to 0.4 micron).

Another object is to provide an UV imaging system, useful as a microscope
10 or as micro-lithography optics, with a large numerical aperture of 0.9 and with a field of view of at least one millimeter. The system is preferably tele-centric.

The invention is a high performance, high numerical aperture, ultra-broad spectral region catadioptric optical system with zooming capability, comprising an all-refractive zooming tube lens section with one collimated conjugate,
15 constructed so that during zooming its higher-order chromatic aberrations (particularly higher-order lateral color) do not change; and a non-zooming high numerical aperture catadioptric objective section which compensates for the uncorrected (but stationary during zoom) higher-order chromatic aberration residuals of the zooming tube lens section.

These and other objects and advantages of the present invention will
20 become apparent to those skilled in the art from the following detailed description and accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a prior art system that completely corrects for primary, secondary and tertiary axial color over a broad wavelength band in the near and deep
5 ultraviolet (0.2 micron to 0.4 micron), but not for residual lateral color;

FIG. 2 is a modified version of the '976 Shafer patent optimized for use in .193 micron wavelength high power excimer laser applications;

FIG. 3 is a schematic side view of a catadioptric imaging system in accord with the parent application;

10 FIG. 4 is a schematic side view of a catadioptric imaging system in accordance with the present invention;

FIG. 5 is schematic side view of a catadioptric imaging system in the three positions having 36X, 64X and 100X power magnifications in accordance with a first embodiment of the invention;

15 FIG. 6 is a schematic side view of a catadioptric imaging system in three positions having 36X, 64X and 100X power magnifications in accordance with a second embodiment of invention;

FIG. 7 is a schematic side view of a catadioptric imaging system in three positions having 36X, 64X and 100X power magnification in accordance with a
20 third embodiment of the invention; and

FIG. 8 is a schematic side view of a zooming catadioptric imaging system in an application for the inspection of semiconductor wafers.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIG. 3 shows a catadioptric imaging system of the parent invention, which is especially suited for use in broadband deep ultraviolet applications and is made up of a focusing lens group 11 for forming an intermediate image 13, a field lens group 15 disposed proximate to the intermediate image 13 for correcting chromatic aberrations, and a catadioptric group 17 for focusing light from the intermediate image 13 to a final image 19. The imaging system is optimized to correct both monochromatic (Seidel) aberrations and chromatic aberrations (longitudinal and lateral), as well as chromatic variations of the monochromatic aberrations, over a wavelength band that extends into the deep ultraviolet (UV) portion of the spectrum, covering 0.20 to 0.40 micron UV light. The catadioptric system of the parent invention can be adapted for a number of UV imaging applications, including as a UV microscope objective, a collector of surface scattered UV light in a wafer inspection apparatus, or as mask projection optics for a UV photolithography system.

The focusing lens group 11 in FIG. 3 consists of seven lens elements 21-27, with two of the lens elements (21 and 22) separated by a substantial distance from the remaining five lens elements (23-27). The separations of the pair of lens elements 21 and 22 from the remaining five lens elements 23-27 is typically on the order of at least one-half the total combined thickness of the five lens elements 23-27. For example, lens elements 23-27 may span a distance of about 60 millimeters (mm) and lens element 22 may be 30 to 60 mm from lens element 23. The actual dimensions depend on the scale chosen for the embodiment. The two lenses 21 and 22 form a low power doublet for correcting chromatic variation of monochromatic image aberrations, such as coma and astigmatism. By having this doublet 21 and 22 relatively far from the other system components, the shift of the light beam with field angles on these two lenses is maximized. That in turn

helps greatly in achieving the best correction of chromatic variation of aberrations.

The five lenses 23-27 of the main focusing subgroup consist of a thick strong negative meniscus lens 23, an opposite-facing strongly-curved negative meniscus lens 24, a strong bi-convex lens 25, a strong positive meniscus lens 26, and an opposite-facing strongly-curved, but very weak, meniscus lens 27 of either positive or negative power. Variations of this lens 23-27 subgroup are possible. The subgroup focuses the light to an intermediate image 13. The curvature and positions of the lens surfaces are selected to minimize monochromatic aberrations and to cooperate with the doublet 21-22 to minimize chromatic variations of those aberrations.

The field lens group 15 typically comprises an achromatic triplet, although any achromatized lens group can be used. Both fused silica and CaF_2 glass materials are used. Other possible deep UV transparent refractive materials can include MgF_2 , SrF_2 , LaF_3 and LiF glasses, or mixtures thereof. In addition to refractive materials, diffractive surfaces can be used to correct chromatic aberrations. Because the dispersions between the two UV transmitting materials, CaF_2 glass and fused silica, are not very different in the deep ultraviolet, the individual components of the group 15 have strong curvatures. Primary color aberrations are corrected mainly by the lens elements in the catadioptric group 17 in combination with the focusing lens group 11. Achromatization of the field lens group 15 allows residual lateral color to be completely corrected.

The catadioptric group 17 of FIG. 3 includes a fused silica meniscus lens 39 with a back surface having coating 41, and fused silica lens 43 with a back surface having a reflective coating 45. The two lens elements 39 and 43 front surfaces face each other. The reflective surface coating 41 and 45 are typically aluminum, possibly with a dielectric overcoat to enhance reflectivity.

The first lens 39 has a hole 37 centrally formed therein along the optical axis of the system. The reflective coating 41 likewise ends at the central hole 37 leaving a central optical aperture through which light can pass unobstructed by

either the lens 39 or its reflective coating 41. The optical aperture defined by the hole 37 is in the vicinity of the intermediate image plane 13 so that there is minimum optical loss. The achromatic field lens group 15 is positioned in or near the hole 37. The second lens 43 does not normally have a hole, but there is a centrally located opening or window 47 where the coating is absent on the surface reflective coating 45. The optical aperture in lens 39 with its reflective coating 41 need not be defined by a hole 37 in the lens 39, but could be defined simply by a window in the coating 41 as in coating 45. In that case, light would pass one additional time through the refractive surfaces of lens 39.

10 Light from the source transmitted along the optical axis toward the intermediate image plane 13 passes through the optical aperture 37 in the first lens 39 and then through the body of the second lens 43 where it is reflected by the near planar (or planar) mirror coating 45 back through the body of the second lens 43. The light then passes through the first lens 39, is reflected by the mirror
15 surface 41 and passes back through the first lens 39. Finally the light, now strongly convergent passes through the body of the second lens 43 for a third time, through the optical aperture 47 to the target image plane adjacent aperture 47. The curvatures and positions of the first and second lens surfaces are selected to correct primary axial and lateral color in conduction with the focal lens group
20 11.

For a flexible deep UV microscope system, it is important to provide various magnifications, numerical apertures, field sizes, and colors. In principle, an UV microscope system can comprise several catadioptric objectives, tube lenses, and zoom lenses. However, several problems are encountered when
25 designing a complete microscope system. First, the microscope design needs to accommodate many large size catadioptric objectives to provide different magnifications and numerical apertures. Second, in order to maintain image quality, chromatic variation of aberrations of each tube lens must be corrected to the same degree as the objective itself. Third, the chromatic variation of

aberrations of a zooming system must be corrected over the full range of zoom. These problems are addressed by the present invention.

An ultra-broadband UV microscope imaging system according to the present invention as illustrated in FIG. 4 comprises a catadioptric objective section 128 and a zooming tube lens group sections 139. The catadioptric objective section 128 comprises a catadioptric lens group 122, a field lens group 127, a focusing lens group 129. The beam splitter 132 provides an entrance for the UV light source. The aperture stop 131 is used to adjust the system imaging numerical aperture (NA). The microscope system images an object 120 (e.g., a wafer being inspected) to the image plane 140. The complete 0.9 NA catadioptric objective section 128 is also described in the parent patent application.

The catadioptric objective section 128 is optimized for ultra-broadband imaging in the UV spectral region (about 0.20 to 0.40 micron wavelength). It has excellent performance for high numerical apertures and large object fields. This invention uses the Schupmann principle in combination with an Offner field lens to correct for axial color and first order lateral color, and an achromatized field lens group to correct the higher order lateral color. The elimination of the residual higher order chromatic aberrations makes the ultra-broadband UV objective design possible.

The catadioptric lens group 122 includes a near planar or planar reflector 123, which is a reflectively coated lens element, a meniscus lens 125, and a concave spherical reflector. Compared to the reflectively coated lens element 39 in FIG. 3, the preferred embodiment uses a concave reflector 124 and a large meniscus lens 125 to simplify manufacturing. Both reflective elements have central optical apertures without reflective material to allow light from the intermediate image plane 126 to pass through the concave reflector, be reflected by the near planar (or planar) reflector 123 onto the concave reflector 124, and pass back through the near planar (or planar) reflector 123, traversing the associated lens element or elements on the way.

The achromatic multi-element field lens group 127 is made from two or more different refractive materials, such as fused silica and fluoride glass, or diffractive surfaces. The field lens group 127 may be optically coupled together or alternatively may be spaced slightly apart in air. Because fused silica and fluoride glass do not differ substantially in dispersion in the deep ultraviolet range, the individual powers of the several component element of the field lens group need to be of high magnitude. Use of such an achromatic field lens allows the complete correction of axial color and lateral color over an ultra-broad spectral range. In the simplest version of the design, only one field lens component need be of a refractive material different than the other lenses of the system. Compared to group 15 in FIG. 3, the field lens group 127 is moved slightly from the intermediate image location to reduce the heat load and surface scattering of the field lens group.

The present invention has a focusing lens group 129 with multiple lens elements, preferably all formed from a single type of material, with refractive surfaces having curvatures and positions selected to correct both monochromatic aberrations and chromatic variation of aberrations and focus light to an intermediate image. In the focusing lens group 129 a special combination of lenses 130 with low power corrects the system for chromatic variation in spherical aberration, coma, and astigmatism.

Design features of the field lens group 127 and the low power group 130 are key to the present invention. The zooming tube lens 139 combined with the catadioptric objective 128 provides many desirable features. Such an all-refractive zooming lens ideally will allow the detector array 140 to be stationary during zooming, although the invention is not limited to this preferred embodiment. Assuming that the catadioptric objective system 128 does not also have any zooming function, there are two design possibilities open to the zooming tube lens system 139.

First, the zooming section 139 can be all the same refractive material, such as fused silica, and it must be designed so that primary longitudinal and primary

lateral color do not change during zooming. These primary chromatic aberrations do not have to be corrected to zero, and cannot be if only one glass type is used, but they have to be stationary, which is possible. Then the design of the catadioptric objective 128 must be modified to compensate for these
5 uncorrected but stationary chromatic aberrations of the zooming tube lens. This can be done, but a solution is needed with good image quality. Despite the limited image quality, this design possibility is very desirable since the whole combined microscope system is a single material, i.e., fused silica, except for the calcium fluoride or a diffractive surface in the achromatized Offner-type field
10 lens.

Second, the zooming tube lens group 139 can be corrected for aberrations independently of the catadioptric objective 128. This requires the use of at least two refractive materials with different dispersions, such as fused silica and calcium fluoride, or diffractive surfaces. Unfortunately, the result is a tube lens
15 system that, because of unavoidable higher-order residuals of longitudinal and lateral color over the entire zoom range, is not capable of high performance over a very broad UV spectral region. Compromises must then be made in the form of reducing the spectral range, the numerical aperture, the field size of the combined system, or some combination of these compromises. The result is that
20 the very high capabilities of the catadioptric objective cannot be duplicated with an independently corrected zooming tube lens.

The present invention straddles the two situations just described. The zooming tube lens 139 is first corrected independently of the catadioptric objective 128, using two refractive materials (such as fused silica and calcium
25 fluoride). Lens 139 is then combined with the catadioptric objective 128 and then the catadioptric objective is modified to compensate for the residual higher-order chromatic aberrations of the zooming tube lens system. This is possible because of the design features of the field lens group 127 and the low power lens group 130 of the catadioptric objective described earlier. The combined system is then
30 optimized with all parameters being varied to achieve the best performance.

One unique feature of the present invention is the particular details of the zooming tube lens. If the higher-order residual chromatic aberrations of this zooming system change during zoom, then the catadioptric objective cannot exactly compensate for them except at one zoom position. It is easy to design a zooming tube lens system where the low-order chromatic aberrations do not change during zoom, and are corrected to zero as well. But it is very difficult to find a zooming tube lens design where the higher-order chromatic aberration residuals (which are uncorrectable to zero, in that system by itself) do not change during the zooming.

10 A tube lens section can be designed such that its higher-order chromatic aberrations do not change by any significant amount during zoom. If the detector array 140 is allowed to move during zoom, then the design problem becomes much easier, but that is not nearly as desirable as having an image position fixed relative to the rest of the system.

15 The imaging system of the invention provides a zoom from 36X to 100X and greater, and integrates objectives, turret, tube lenses (to provide more magnifications) and zoom optics into one module. The imaging system reduces optical and mechanical components, improves manufacturability and reduces production costs. The imaging system has several performance advantages such as: high optical resolution due to deep UV imaging, reduced thin film interference effects due to ultra-broadband light, and increased light brightness due to integration of ultra-broad spectral range. The wide range zoom provides continuous magnification change. The fine zoom reduces aliasing and allows electronic image processing, such as cell-to-cell subtraction for a repeating image array. By placing an adjustable aperture in the aperture stop of the microscope system one can adjust the NA and obtain the desired optical resolution and depth of focus. The invention is a flexible system with an adjustable wavelength, an adjustable bandwidth, an adjustable magnification, and an adjustable numerical aperture.

There are three possible embodiments of zoom lenses. The first embodiment provides linear zoom motion with a fixed detector array position. The second embodiment provides linear zoom motion with a moving detector array position. The third embodiment, in addition to zoom lenses, utilizes folding mirrors to reduce the physical length of the imaging system and fix the detector array position.

The first embodiment of zoom lenses provides linear zoom motion with a fixed detector array position. FIG. 5 shows the 36X zoom arrangement of the lenses, the 64X zoom arrangement of the lenses and the 100X zoom arrangement of the lenses. The detector array 140 (not shown) is fixed. The zooming tube lens design 141 is comprised of two moving lens groups 142 and 143. The beam splitter is not shown in this and later figures for the purpose of clarity. The following table lists the surfaces shown in FIG. 5, where the surface numbering begins at "0" for the final image counting towards the object being inspected.

Lens Data for the First Embodiment

0.90 N.A., fixed detector, 36X - 100X zoom, 1.0 mm field size

Surface	Radius	Thickness	Glass
0	--	30.000000 36X 152.396279 64X 318.839746 100X	Air
1	-46.843442	4.000000	Calcium fluoride
2	67.017379	0.999804	Air
3	122.003494	7.000000	Silica
4	-34.944144	4.496612	Air
5	-42.883889	4.000000	Calcium fluoride
6	-1.5857e+03	339.659737 36X 298.114540 64X 279.997392 100X	Air

7	-657.423731	9.000000	Calcium fluoride
8	-67.124645	0.999689	Air
9	-70.484550	6.000000	Silica
10	102.732012	28.382549	Air
11	170.942101	13.000000	Calcium fluoride
12	-126.768482	274.177371 36X 193.326289 64X 44.999970 100X	Air
13	103.846671	5.000000	Silica
14	57.151413	3.500000	Air
15	113.406488	7.000000	Silica
16	-149.254887	58.301706	Air
17	41.730749	14.904897	Silica
18	17.375347	11.364798	Air
19	-22.828011	5.892666	Silica
20	-57.773872	1.000000	Air
21	174.740180	7.000000	Silica
22	-48.056749	4.000000	Air
23	24.023380	11.500000	Silica
24	-1.0394e+03	4.198255	Air
25	-43.531092	5.000000	Silica
26	-197.030499	1.000000	Air
27	45.618003	29.827305	Silica
28	-81.744432	1.662262	Air
29	17.258988	4.000000	Calcium fluoride
30	-31.010978	0.315372	Air
31	-24.055515	2.000000	Silica
32	5.602559	0.020000	Air
33	5.602559	8.318486	Calcium fluoride

34	-24.871116	7.710304	Air
35 Aperture Stop	--	8.328925	Air
36	85.000000	11.000000	Silica
37	70.542512	29.938531	Air
38	1.6514e+03	10.000000	Silica
39	Infinity	-10.000000	Reflect
40	1.6514e+03	-29.938531	Air
41	70.542512	-11.000000	Silica
42	85.000000	-8.328925	Air
43	74.648515	8.328925	Reflect
44	85.000000	11.000000	Silica
45	70.542512	29.938531	Air
46	1.6514e+03	10.000000	Silica
47	Infinity	1.500000	Air

The second embodiment of zoom lenses provides linear zoom motion with a moving detector array position and FIG. 6 shows the 36X zoom arrangement of the lenses, the 64X zoom arrangement of the lenses and the 100X zoom arrangement of the lenses. The following table lists the surfaces shown in FIG. 6, where the surface numbering begins at "0" for the final image incrementing by 1 towards the object being inspected.

10

Lens Data for the Second Embodiment

0.90 N.A., moving detector, 36X to 100X zoom, 1.0 mm field size

SURFACE	RADIUS	THICKNESS	GLASS
---------	--------	-----------	-------

0	Infinity	110.004950 36X 405.371660 64X 785.131189 100X	Air
1	73.156621	5.000000	Calcium fluoride
2	-609.638437	18.230155	Air
3	-30.303090	3.500000	Calcium fluoride
4	44.361656	4.000000	Air
5	-51.318999	7.765282	Silica
6	-23.231195	1.564401	Air
7	-119.756315	4.000000	Calcium fluoride
8	40.002701	12.019418	Air
9	54.594789	10.000000	Calcium fluoride
10	-28.923744	0.100000	Air
11	-29.957411	5.000000	Silica
12	-156.281481	202.434836 36 X 108.230318 64X 64.650627 100X	Air
13	188.664770	4.500000	Silica
14	56.034008	3.500000	Air
15	214.395300	6.000000	Silica
16	-79.842174	62.685096	Air
17	29.721624	10.000000	Silica
18	18.529920	11.406390	Air
19	-23.406055	5.864347	Silica
20	-46.076628	1.000000	Air
21	94.310969	7.000000	Silica
22	-75.041727	4.000000	Air
23	23.509091	11.500000	Silica
Aperture stop			

24	-399.710365	4.516455	Air
25	-42.987793	10.000000	Silica
26	-217.407455	12.083912	Air
27	24.940148	10.000000	Calcium fluoride
28	-177.604306	0.100000	Air
29	24.508018	10.000000	Calcium fluoride
30	-54.909641	0.664880	Air
31	-16.389836	2.000000	Silica
32	4.296836	0.020000	Air
33	4.296836	3.000000	Calcium fluoride
34	-14.014264	7.000000	Air
35	--	11.160093	--
Internal image			
36	102.631452	11.000000	Silica
37	84.741293	27.845569	Air
38	1.1470e+03	10.000000	Silica
39	Infinity	-10.000000	Reflect
40	1.1470e+03	-27.845569	Air
41	84.741293	-11.000000	Silica
42	102.631452	-11.160093	Air
43	75.033466	11.160093	Reflect
44	102.631452	-11.000000	Silica
45	84.741293	27.845569	Air
46	1.1470e+03	10.000000	Silica
47	Infinity	1.500000	Air

The third embodiment of zoom lenses provides linear zoom motion with a fixed sensor position by using the same lens design as the second embodiment and incorporating a "trombone" system of reflective elements so that the detector array does not move. FIG. 7 shows the 36X zoom arrangement of the lenses and reflective elements, the 64X zoom arrangement of the lenses and reflective elements and the 100X zoom arrangement of the lenses and reflective elements. The folding mirror group 144 is the "trombone" system of reflective elements. This folding mirror arrangement is just one example. Many other arrangements are possible, such as, using a different number of reflective elements.

Module Transfer Function curves (not shown) indicate that the FIG. 7 embodiment is essentially perfect at 64X and 100X, and is good at 36X. Zooming is done by moving a group of 6 lenses, as a unit, and also moving the arm of the trombone slide. Since the trombone motion only affects focus and the f# speed at this location is very slow, the accuracy of this motion could be very loose. One advantage of the trombone embodiment is that it significantly shortens the system. Another advantage is that there is only one zoom motion that involves active (non-flat) optical elements. And the other zoom motion, with the trombone slide, is insensitive to errors.

FIG. 8 is a schematic side view of a catadioptric imaging system with a zoom in an application for the inspection of semiconductor wafers. Platform 80 holds a wafer 82 that is composed of several integrated circuit dice 84. The catadioptric objective 86 transfers the light ray bundle 88 to the zooming tube lens 90 which produces an adjustable image received by the detector 92. The detector 92 converts the image to binary coded data and transfers the data over cable 94 to data processor 96.

The exemplary embodiments described herein are for purposes of illustration and are not intended to be limiting. Therefore, those skilled in the art will recognize that other embodiments could be practiced without departing from the scope and spirit of the claims set forth below.

WE CLAIM:

1. A high numerical aperture, broad spectral region catadioptric optical system comprising:
 - 5 a tube lens section which can zoom or change magnification without changing its higher-order chromatic aberrations over a plurality of wavelengths, including at least one wavelength in the UV range; and a non-zooming high numerical aperture catadioptric objective lens section.
- 10 2. A system as in claim 1 wherein said lens sections use fused silica and calcium fluoride.
3. A system as in claim 1 wherein said lens sections use diffractive surfaces.
- 15 4. A system as in claim 1 further comprising a detector array which does not move during zooming or a change in magnification of said tube lens section.
5. A system as in claim 1 wherein said objective lens section comprises an achromatized field lens group which eliminates residual chromatic aberrations.
 - 20 and compensates said tube lens section for higher-order chromatic aberrations, and wherein the combination of said lens sections corrects for chromatic variations in spherical aberration, coma, and astigmatism.
6. A high resolution, broadband UV imaging system comprising:
 - 25 a detector array;
 - a broadband UV radiation source; and
 - a high numerical aperture catadioptric optical system capable of broadband UV zooming or a magnification change which maintains focus over a range of ultraviolet wavelengths on said detector array.

7. A system as in claim 6 wherein said detector array remains stationary during zooming.

8. A system as in claim 6 wherein said catadioptric optical system includes
5 an objective lens section with compensation means for achromatizing a field lens group to eliminate residual chromatic aberrations and thereby compensate said tube lens section for higher-order chromatic aberrations, and wherein the combination of said lens sections corrects for chromatic variations in spherical aberration, coma, and astigmatism.

10

9. A high numerical aperture, broad spectral region catadioptric optical system comprising:

a focusing lens group including a plurality of lens elements, with lens surfaces thereof disposed at first predetermined positions along an optical path
15 of the system and having curvatures and said positions selected to focus ultraviolet light at an intermediate image within the system, and simultaneously to also provide in combination with the rest of the system, high levels of correction of both image aberrations and chromatic variation of aberrations over a wavelength band including at least one wavelength in the UV range;

20 a field lens group with a net positive power aligned along said optical path proximate to said intermediate image, the field lens group including a plurality of lens elements with different dispersions, with lens surfaces disposed at second predetermined positions and having curvatures selected to provide substantial correction of chromatic aberrations including at least secondary
25 longitudinal color and primary and secondary lateral color of the system over said wavelength band;

a catadioptric relay group, including a combination of at least two reflective surfaces and at least one refractive surface disposed at third predetermined positions and having curvatures selected to form a real image of
30 said intermediate image, such that, in combination with said focusing lens group,

primary longitudinal color of the system is substantially corrected over said wavelength band; and

a zooming tube lens group which can zoom or change magnification without changing its higher-order chromatic aberrations, and with lens surfaces thereof disposed at fourth predetermined positions along an optical path of the system, wherein at least one of the non-zooming groups of the high numerical aperture catadioptric optical system substantially compensates over said wavelength band for uncorrected, but stationary higher-order chromatic aberration residuals of the zooming tube lens group.

10

10. A high numerical aperture, broad spectral region catadioptric optical system as described in claim 1 wherein said tube lens group which can zoom or change magnification without substantially changing its higher-order chromatic aberrations.

15

11. A high numerical aperture, broad spectral region catadioptric optical system as described in claim 1 wherein said tube lens group includes at least one diffractive lens.

20

12. A system as in claim 6 wherein said catadioptric optical system maintains near-diffraction-limited image quality over a magnification range of said system and over a UV spectral range sensed by said detector array.

25

13. A high numerical aperture, broad spectral region catadioptric optical system as described in claim 9 wherein said tube lens group can zoom or change magnification without substantially changing its higher-order chromatic aberrations.

14. A high numerical aperture, broad spectral region catadioptric optical system as described in claim 9 wherein said zooming tube lens group comprises at least one diffractive lens.
- 5 15. A high numerical aperture, broad spectral region catadioptric optical system as described in claim 9:
wherein said field lens group includes a plurality of lens elements formed from at least two different refractive materials with different dispersions.
- 10 16. A high resolution, broadband UV imaging system comprising:
a detector array;
a broadband UV radiation source including a ultraviolet wavelength band of at least 0.23 - 0.29 microns; and
a high numerical aperture catadioptric optical system capable of
15 broadband UV zooming which maintains near-diffraction-limited image quality on said detector array.
17. A system as in claim 16 wherein said catadioptric optical system maintains near- diffraction-limited image quality over a magnification range of said system
20 and over a UV spectral range sensed by said detector array.
18. A system as in claim 16 wherein said catadioptric optical system includes an objective lens section with compensation means for achromatizing a field lens and substantially eliminating residual chromatic aberrations and thereby
25 substantially compensate said tube lens section for higher-order chromatic aberrations, and wherein the combination of said lens sections substantially corrects for chromatic variations in spherical aberration, coma, and astigmatism.
19. A high numerical aperture, broad spectral region catadioptric optical
30 system comprising:

a focusing lens group including a plurality of lens elements, with refractive surfaces having curvatures and positions selected to focus ultraviolet light at an intermediate image within the system, and simultaneously to also provide in combination with the rest of the system, high levels of correction of both image aberrations and chromatic variation of aberrations over a wavelength band including at least one wavelength in the UV range;

a field lens group with a net positive power aligned along said optical path proximate to said intermediate image, the field lens group including a plurality of lens elements, with refractive surfaces having curvatures selected to provide substantial correction of chromatic aberrations including at least secondary longitudinal color and primary and secondary lateral color of the system over said wavelength band;

a catadioptric relay group, including a combination of at least two reflective surfaces and at least one refractive surface having curvatures selected to form a real image of said intermediate image, such that, in combination with said focusing lens group, primary longitudinal color of the system is substantially corrected over said wavelength band; and

a tube lens group which can zoom or change magnification without changing its higher-order chromatic aberrations, and with refractive surfaces, wherein at least one of the non-zooming groups of the high numerical aperture catadioptric optical system substantially compensates over said wavelength band for uncorrected, but stationary higher-order chromatic aberration residuals of the zooming tube lens group.

20. A high numerical aperture, broad spectral region catadioptric optical system as described in claim 19 wherein said tube lens group is an all-refractive zooming tube lens group which can zoom or change magnification without changing its higher-order chromatic aberrations.

21. A high numerical aperture, broad spectral region catadioptric optical system as described in claim 19 wherein said tube lens group is a zooming tube lens group with at least one diffractive lens.
- 5 22. A high resolution, broadband UV imaging system comprising:
a detector array which can receive an image over a range of ultraviolet wavelengths;
a broadband UV radiation source providing a ultraviolet wavelength band; and
10 a catadioptric optical system comprising:
a focusing lens group including a plurality of lens elements, with refractive surfaces having curvatures and positions selected to focus ultraviolet light at an intermediate image within the system, and simultaneously to also provide in combination with the rest of the system,
15 high levels of correction of both image aberrations and chromatic variation of aberrations over a wavelength band including one wavelength in the UV range,
a field lens group proximate to said intermediate image, the field lens group including a plurality of lens elements with refractive surfaces
20 having curvatures selected to provide substantial correction of chromatic aberrations including at least secondary longitudinal color and primary and secondary lateral color of the system over said wavelength band,
a catadioptric relay group, including a combination of at least two reflective surfaces and at least one refractive surface having curvatures
25 selected to form a real image of said intermediate image, such that, in combination with said focusing lens group, primary longitudinal color of the system is substantially corrected over said wavelength band, and
a zooming tube lens group which can zoom or change magnification without changing its higher-order chromatic aberrations,
30 and with a plurality of refractive surfaces, wherein at least one of the non-

zooming groups of the high numerical aperture catadioptric optical system substantially compensates over said wavelength band for uncorrected, but stationary higher-order chromatic aberration residuals of the zooming tube lens group.

5

23. A system as in claim 22 wherein said detector array remains stationary during zooming or a change in magnification.

24. A system as in claim 22 wherein said catadioptric optical system includes compensation means for achromatizing a field lens and substantially eliminating residual chromatic aberrations and thereby substantially compensate said zooming tube lens group for higher-order chromatic aberrations, and wherein the combination of said lens groups substantially corrects for chromatic variations in spherical aberration, coma, and astigmatism over said wavelength band.

15

25. A high numerical aperture, broad spectral region catadioptric optical system comprising:

a focusing lens group including a plurality of lens elements, with refractive surfaces thereof disposed to focus ultraviolet light within the system, and simultaneously to also provide in combination with the rest of the system, high levels of correction of both image aberrations and chromatic variation of aberrations over a wavelength band including at least one wavelength in the UV range;

25 a field lens group with a net positive power, the field lens group including a plurality of lens elements, with refractive surfaces having curvatures selected to provide substantial correction of chromatic aberrations including at least secondary longitudinal color and primary and secondary lateral color of the system over said wavelength band;

- a zooming tube lens section which can zoom or change magnification without substantially changing its higher-order chromatic aberrations; and
- a non-zooming catadioptric objective lens section which provides means for substantially compensating for uncorrected, but stationary higher-order chromatic aberration residuals of said zooming tube lens section.

26. A system as in claim 25 wherein said catadioptric objective lens section comprises compensation means for achromatizing a field lens and for substantially eliminating residual chromatic aberrations and thereby substantially compensate said tube lens section for higher-order chromatic aberrations, and wherein the combination of said lens sections substantially corrects for chromatic variations in spherical aberration, coma, and astigmatism over said wavelength band.

27. A system as in claim 25 wherein at least one of said lenses in the field lens group comprises a lens made of fused silica.

28. A system as in claim 25 wherein at least one of said lenses in the field lens group comprises a lens made of calcium fluoride.

29. A high numerical aperture, broad spectral region catadioptric optical system as described in claim 25 further comprising an all-refractive zooming tube lens group which can zoom or change magnification without substantially changing its higher-order chromatic aberrations.

30. A high numerical aperture, broad spectral region catadioptric optical system as described in claim 25 further comprising a zooming tube lens group with at least one diffractive lens.

31. A method for constructing a high numerical aperture, broad spectral region catadioptric optical system comprising the steps of:

providing a focusing lens group including a plurality of lens elements, with refractive surfaces thereof disposed at first predetermined positions along an optical path of the system and having curvatures and said positions selected to focus ultraviolet light at an intermediate image within the system, and simultaneously to also provide in combination with the rest of the system, high levels of correction of both image aberrations and chromatic variation of aberrations over a wavelength band including at least one wavelength in the UV range;

providing a field lens group with a net positive power aligned along said optical path proximate to said intermediate image, the field lens group including a plurality of lens elements formed from at least two different refractive materials with different dispersions, with refractive surfaces of the lens elements of the field lens group disposed at second predetermined positions and having curvatures selected to provide substantial correction of chromatic aberrations including at least secondary longitudinal color and primary and secondary lateral color of the system over said wavelength band;

forming a real image with a catadioptric relay group, including a combination of at least two reflective surfaces and at least one refractive surface disposed at third predetermined positions and having curvatures selected to form a real image of said intermediate image, such that, in combination with said focusing lens group, primary longitudinal color of the system is substantially corrected over said wavelength band; and

zooming with a zooming tube lens group which can zoom or change magnification without changing its higher-order chromatic aberrations, and with lens surfaces thereof disposed at fourth predetermined positions along an optical path of the system, wherein at least one of the non-zooming groups of the high numerical aperture catadioptric optical system substantially compensates over

said wavelength band for uncorrected, but stationary higher-order chromatic aberration residuals of the zooming tube lens group.

32. A method for constructing a high numerical aperture, broad spectral
5 region catadioptric optical system as in claim 31 further comprising the step of:
constructing a catadioptric objective lens section comprising compensation
means for achromatizing a field lens and for substantially eliminating residual
chromatic aberrations and thereby substantially compensate said tube lens
section for higher-order chromatic aberrations, and wherein the combination of
10 said lens sections substantially corrects for chromatic variations in spherical
aberration, coma, and astigmatism over said wavelength band.

33. A method of imaging an object with a high numerical aperture, broad
spectral region catadioptric optical system comprising:
15 zooming with a zooming tube lens group which can zoom or change
magnification without changing at least a portion of its chromatic aberrations;
and
imaging said object with a non-zooming high numerical aperture
catadioptric objective lens section which substantially compensates for
20 uncorrected, but stationary higher-order chromatic aberration residuals of the
zooming tube lens group.

34. A high numerical aperture, broad spectral region catadioptric optical
system comprising:
25 a zooming tube lens group which can zoom or change magnification
without changing at least a portion of its chromatic aberrations; and
a non-zooming high numerical aperture catadioptric objective lens section which
substantially compensates for uncorrected, but stationary higher-order chromatic
aberration residuals of the zooming tube lens group.

1/7




FIG. 1
Prior Art




FIG. 2
Prior Art

2/7




FIG. 3





FIG. 4

FIG. 5



5/7

FIG. 6





FIG. 7



7/7




FIG. 8

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: G02B 15/14, 17/08, 22/00		(11) International Publication Number: WO 99/08134
A3		(43) International Publication Date: 18 February 1999 (18.02.99)
(21) International Application Number: PCT/US98/16568		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 7 August 1998 (07.08.98)		
(30) Priority Data: 08/908,247 7 August 1997 (07.08.97) US		
(71) Applicant: KLA-TENCOR, INC. [US/US]; 160 Rio Robles, San Jose, CA 95161-1809 (US).		
(72) Inventors: SHAFER, David, Ross; 56 Drake Lane, Fairfield, CT 06430 (US). CHUANG, Yung-Ho; 10679 Farallone Drive, Cupertino, CA 95014 (US). TSAI, Bin-Ming, Benjamin; 19801 Scotland Drive, Saratoga, CA 95070 (US).		
(74) Agents: FERRELL, John, S. et al.; Carr & Ferrell LLP, Suite 200, 2225 East Bayshore Road, Palo Alto, CA 94303 (US).		<p>Published</p> <p>With international search report.</p> <p>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p> <p>(88) Date of publication of the international search report: 29 April 1999 (29.04.99)</p>

(54) Title: ULTRA-BROADBAND UV MICROSCOPE IMAGING SYSTEM WITH WIDE RANGE ZOOM CAPABILITY



(57) Abstract

An ultra-broadband ultraviolet (UV) catadioptric imaging microscope system with wide-range capability. The microscope system, which comprises a catadioptric lens group (128) and a zooming tube lens group (139), has high optical resolution in the deep UV wavelengths, continuously adjustable magnification, and a high numerical aperture. The system integrates micro-manufacturing process. The preferred embodiment offers excellent image quality across a very broad deep ultraviolet spectral range, combined with an all-refractive zooming tube lens. The zooming tube lens is modified to compensate for higher-order chromatic aberrations that would normally limit performance.

INTERNATIONAL SEARCH REPORT

International application No.
PCT:US98/16568

A. CLASSIFICATION OF SUBJECT MATTER IPC(6) : G02B 15/14, 17/08, 22/00 US CL : 359/351, 354, 357, 365, 432; 250/372 According to International Patent Classification (IPC) or to both national classification and IPC																									
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 359/354, 357, 365, 432, 355, 356, 364, 366, 676, 422, 728, 729, 730; 250/372 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) APS search terms: catadioptric, catoptric, catadioptric, catoptric, ultraviolet, UV, zoom, detect?																									
C. DOCUMENTS CONSIDERED TO BE RELEVANT																									
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.																							
X ----- A	US 4,988,858 A (PINSON) 29 January 1991 (29.01.91) see entire document	6,7 ----- 1-5, 8-34																							
X	US A 4,971,428 (MOSKOVICH) 20 November 1990 (20.11.90) see entire document	33, 34																							
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.																									
<table border="0"><tr><td>* Special categories of cited documents:</td><td>*T</td><td>later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td></tr><tr><td>*A</td><td>document defining the general state of the art which is not considered to be of particular relevance</td><td>*X</td><td>document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td></tr><tr><td>*B</td><td>earlier document published on or after the international filing date</td><td>*Y</td><td>document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td></tr><tr><td>*L</td><td>document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td><td>*A</td><td>document member of the same patent family</td></tr><tr><td>*O</td><td>document referring to an oral disclosure, use, exhibition or other means</td><td></td><td></td></tr><tr><td>*P</td><td>document published prior to the international filing date but later than the priority date claimed</td><td></td><td></td></tr></table>			* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	*A	document defining the general state of the art which is not considered to be of particular relevance	*X	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	*B	earlier document published on or after the international filing date	*Y	document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	*L	document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A	document member of the same patent family	*O	document referring to an oral disclosure, use, exhibition or other means			*P	document published prior to the international filing date but later than the priority date claimed		
* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention																							
*A	document defining the general state of the art which is not considered to be of particular relevance	*X	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone																						
*B	earlier document published on or after the international filing date	*Y	document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art																						
*L	document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A	document member of the same patent family																						
*O	document referring to an oral disclosure, use, exhibition or other means																								
*P	document published prior to the international filing date but later than the priority date claimed																								
Date of the actual completion of the international search 26 FEBRUARY 1999		Date of mailing of the international search report 11 MAR 1999																							
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20531 Facsimile No. (703) 305-3230		Authorized officer JON W. HENRY <i>Jon Lilly</i> Telephone No. (703) 305-6106																							

Form PCT/ISA/210 (second sheet) (July 1992)*

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.